



## Spiral Polyethylene Tubes (2mm – 16mm)

### General Information

Product Name	Spiral Polyethylene Tubes (2mm – 16mm)
Category	RTC Flex (Spiral Tubes)
Material	Polyethylene (PE)
Alternative For	Pneumatic – Automotive – Carwash
Working Pressure	15 - 27 Bar (at 23°C)
Burst Pressure	45 - 80 Bar (at 23°C)
Packaging	Stretch – Box
Origin	Turkey

### Wholesale Volume Tiers

Sample (1 Roll)	Free	In Stock
Pallet (20+ Rolls)	Wholesale Pricing	In Stock
Container (20ft)	Factory Direct Pricing	In Stock

### Chemical Compatibility Guide

Humans	Not detrimental for health
Fuels (Diesel/Petrol)	High 3 (1-5)
Hydraulic Fluid	Resistance
Acids	Depends on Acid Type
Paint	Paint and print available

### Technical Specs

Material Spec	Polyethylene (PE)
Outer Diameter (OD)	To 16 mm (± 0.05 mm)
Inner Diameter (ID)	From 2 mm (± 0.05 mm)
Tube Length	5 – 7.5 – 10 – 15 -20 m
Temp. Range	-20°C to +80°C
Colour	Blue-Red-Yellow-Black-White